

Portable Load Banks



100 kW
208/480V
Suitcase Style
with Transport
case
LB: 69 lbs.
Case:50 lbs.



110 kW
240/480V
HMI control
Casters
160 lbs.



210 kW
240/480V
HMI Control
Casters
250 lbs.



310 kW
240/480V
HMI Control
Casters
375 lbs.



400-600 kW
240/480V
HMI Control
Casters
1320 lbs.



650 kW
240/480V
HMI Control
Casters
1600 lbs.

Standard Options for Portable Load Banks

- Load Cable Sets 10, 25 & 50' available
- Transport Cage (210, 310 & 400-600kW)
- Modbus control (HMI units only)

Permanent Freestanding Load Banks



50-250 kW
208 or 480V
Nema 3r Type
HMI Controller



251-1000 kW
208 or 480V
Nema 3r Type
HMI Controller



1001-2000 kW
480V
Nema 3r Type
HMI Controller



2001-3000 kW
480V
Nema 3r Type
HMI Controller

Standard Options for Freestanding Load Banks

- Site Load Correction (auto load leveling)
- Modbus Control
- 65KAIC rating

Trailer Mounted Solutions



400-600 kW
240 & 480V
Nema 3r Type
HMI Controller
Horizontal Discharge



1001-2000 kW
480V
Nema 3r Type
HMI Controller
Horizontal Discharge



2001-3000 kW
480V
480/240V (reduced capacity)
Nema 3r Type
HMI Controller
Vertical Discharge
Skid Mounted

Standard Options for Trailer Mounted Load Banks

- Available as Trailer Ready
- Powered Cable Reels (max of 2 per trailer)
- Modbus control
- Remote Control